

**Commercial-Grade PC's
for Security Management Applications**



The 3PS line of security servers are commercial-grade PC's designed specifically for use with any third-party security management applications such as IP video management or access control software.

Utilizing a powerful Intel® Mother Board and the Intel® Core™ i5-760 processor delivers measurable advantages including proactive security, energy-efficient performance and remote manageability.

All 3PS Security Servers come standard with Windows 7®, 4GB of DDR3 SDRAM, minimum 5 x USB ports, removable Enterprise-class hard drives, keyboard and mouse. 3PS servers are available in Desktop, 2U and 4U Rackmount chassis.



Features

3PS Commercial-Grade Security Servers

- Available in Desktop, 2U rackmount, and 4U rackmount chassis
- Built with server-class components
- Up to 16TB of storage with optional RAID5
- Intel® Core™ i5-760 processor
- Removable Enterprise-class hard drives
- 1GB NIC
- Includes Keyboard & Mouse
- Pre-loaded with Windows 7®
- 3 year warranty





Server Specifications

PROCESSOR:	Intel® Core™ i5-760
RAM:	4GB DDR3 SDRAM, 1333 MT/s
HARD DRIVE STORAGE:	Desktop: Enterprise Class, removable, up to 4TB 2U: Enterprise Class, removable, up to 6TB 4U: Enterprise Class, removable, up to 16TB
NIC:	1Gbit 1000Base T RJ-45
USB2 PORTS:	Desktop: 5 (2 front, 3 rear) 2U: 8 (2 front, 6 rear) 4U: 8 (2 front, 6 rear)
SERIAL CONNECTIONS:	1 serial port
VGA OUTPUT:	1 VGA (DB15), 1 DVI-D (Dual & Quad DVI Graphic Card Upgrades Available)
KEYBOARD & MOUSE:	Yes
OPERATING SYSTEM:	Windows 7®
DIMENSIONS (LxWxH):	Desktop: 7.9" (H) x 10.6" (W) x 13.2" (D) / 20cm (H) x 26.9cm (W) x 33.5cm (D) 2U: 3.5" (H) x 19" (W) x 21.25" (D) / 8.89cm (H) x 48.3cm (W) x 53.975cm (D) 4U: 7" (H) x 19" (W) x 28" (D) / 17.8cm (H) x 48.3cm (W) x 71.7cm (D)
WEIGHT:	Desktop: 20.9 - 22 lbs. / 9.5 - 10 kg 2U: 28.7 - 32.1 lbs. / 13 - 14.6 kg 4U: 31.7 - 35.1 lbs. / 14.38 - 15.9 kg
POWER CONSUMPTION:	Desktop: < 250 watts (150 watts typical) 2U: < 250 watts (150 watts typical) 4U: < 500 watts
REGULATORY:	CE (Class A), FCC (Class A)
OPERATING TEMPERATURE:	40 - 90° F / 4.5 - 35° C
RELATIVE HUMIDITY:	5-95% RH (non-condensing)
INPUT VOLTAGE:	120 VAC
WARRANTY:	3 years, parts and labor

