



UNIFY YOUR SECURITY SOLUTION

Incomlink represents the state of art in receivers.

INC-DTRX-2500 monitoring receiver is ideal and cost-effective to build-up a monitoring station where transmission is sent only through IP/GPRS channel. It provides prominent protection level for reliable and secure operations.

You can have up to 2500 accounts.

Features

- CD Functional hardware receiver without operating system problems
- CO Compact device housing
- 12Vdc power supply (operation through USB in case of power failure)
- **CO** USB connector and RS232
- **Co** Encrypted communication (AES-128)
- C) IP communication monitoring up to 2.500 client accounts
- **CO** IP communication monitoring by client account
- C) Client identification by IP Address / MAC / IMEI
- C) Individual monitoring period settings for each account
- **Continuous** checking of Internet connection
- **CO** Client IP address display in monitoring software
- **CO** Local programming (through USB)
- CD Remote programming (through IP channel)
- **CO** Event list monitoring and filtering from web browser
- C Firmware update function (through serial or IP channel)
- Status displaying through LED signals

Properties

INC-DTRX-2500	
Power Supply	12Vdc at 500mA
Maximum current consumption	about 200mA (on USB: about 100mA)
Event buffer	up to 20,000 events
Ethernet connector	100 Mbit
Operating temperature	+10 °C to +30 °C ; 40% relative humidity
Dimension	110 mm x 190 mm x 35 mm
Weight	0.66 lbs