

INLGTO5IRWA

5.1MP Intelligent Lite ChromaView IR Varifocal Turret Network Camera

- High quality image with 5MP, 1/2.7" CMOS sensor
- True WDR (120 dB) to offer you the best image in the most demanding lighting conditions
- H.265+ & H.264 encoding
- Intelligent People Flow Counting and Crowd Density Monitoring
- Built-in Mic
- Smart IR, up to 40m (131ft) IR distance
- Supports 256 G Micro SD card

Unify your Security Solution

You asked, we listened. Tailored especially for you, Legend is our **fully NDA compliant brand**. It offers our latest technologies in a robust build with edge storage capacity. Legend by Inaxsys provides H.265+ compression and easy installation.

Smart H.265+ & H.264

LEGEND smart encoding technology provides high-quality video with higher efficiency and also reduces the cost of storage space and transmission bandwidth by adopting an advanced algorithm of auto stream control.

Wide Dynamic Range

This camera offers vivid imaging in any scenario. Using industry-leading WDR technology, you'll be able to capture the subject in the most difficult lighting conditions.



**NDA
Compliant**



*Design and specifications are subjects to change without notice.



INLGT05IRWA

5.1MP Intelligent Lite ChromaView IR Varifocal Turret Network Camera

Product Specifications

Camera					
Image Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual, 1 ~ 1/100,000s				
Minimum Illumination	Colour: 0.002 lux (F1.2, AGC ON) 0 lux with IR				
S/N Ratio	More than 56dB				
IR Distance	Distance up to 40m (131ft)				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Wide Dynamic Range	120dB				
Camera Features					
Backlight Compensation	Supported				
White Balance	Auto / Outdoor / Fine Tune / Sodium Lamp / Locked / Auto2				
Digital Noise Reduction	2D/3D DNR				
Flip	Normal / Vertical / Horizontal / 180° / 90° Clockwise / 90° Anti-clockwise				
Defog	Digital Defog				
Privacy Masking	Up to 4 areas				
OSD	Up to 8 OSDs				
HLC	Supported				
Smart IR	Supported				
Day/Night	IR-cut filter with auto switch (ICR)				
ROI	Up to 8 areas				
Lens					
Lens Type	Automatic Focusing and Motorized Zoom Lens				
Focal Length	2.7mm ~ 13.5mm				
Adjustment Angle	Pan: 0° ~ 360°; Tilt: 0° ~ 75°; Rotate: 0° ~ 360°				
Field of View	H: 106.25° ~ 30.42°; V: 56.36° ~ 17.22°; O: 110.34° ~ 34.18°				
DORI Distance	Lens (mm)	Detect	Observe	Recognize	Identify
	2.7	60.8m	24.3m	12.2m	6.1m
	13.5	303.8m	121.5m	60.8m	30.4m
Video					
Compression	H.265+ / H.265 / H.264 / MJPEG				
H.264 code profile	Baseline profile, Main profile, High profile				
Frame Rate	Main Stream: 5MP (2880x1620), Max 30fps; 4MP (2560x1440), Max 30fps; 1080P (1920x1080), Max 30fps 4MP(2560x1440) Max 25fps; 3MP(2304x1296) Max 30fps; 1080P (1920x1080), Max 30fps; 720P(1280x720) Max 30fps				
	Sub Stream: 720P (1280x720), Max 30fps; D1 (720x576), Max 30fps; 640x360, Max 30fps; 2CIF (704x288), Max 30fps; CIF (352x288), Max 30fps				
	Third Stream: D1 (720x576), Max 30fps; 640x360, Max 30fps; 2CIF (704x288), Max 30fps; CIF (352x288), Max 30fps				
Bit Rate	128 Kbps ~ 16 Mbps				

*Design and specifications are subjects to change without notice.



INLGTO5IRWA

5.1MP Intelligent Lite ChromaView IR Varifocal Turret Network Camera

Product Specifications

Network	
Ethernet	1 RJ45 10M/100M Base-TX Ethernet
Protocol	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH
User/Host	Up to 32 users. 2 user levels: administrator, common user and operator
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Compatibility	ONVIF (Profile S, Profile T, Profile G), API, SDK
Management Software	LEGEND VMS, Arkiv
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
	Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
Audio	
Built-in Microphone	Support
Audio Compression	G.711
Audio Bitrate	64 Kbps
Suppression	Support
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD slot, up to 256 GB
Network Storage	ANR
AI	
Smart intrusion prevention	Supports false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection
Statistical Analysis	People counting, support people flow counting and crowd density monitoring
Smart Features	
Detection	Motion detection, Ultra motion detection, Tampering alarm, Audio detection
General Function	Watermark, IP address filtering, tampering alarm, access policy, ARP protection, RTSP authentication, user authentication
Certifications	
Certifications	CE-EMC (EN 55032: 2015+A1:2020, EN 61000-3-3: 2013+A1: 2019, EN IEC 61000-3-2: 2019+A1: 2021, EN 55035: 2017+A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014) CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01) CE-RoHS (2011/65/EU; (EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)
General	
Power Supply	DC 12V±25%, PoE (IEEE 802.3af)
Power Consumption	Less than 7.0W
Working Environment	-30° C to +60° (-22°F ~ 140°F) / Less than 95% RH (non-condensing)
Ingress & Vandal Protection	IP67 & IK10
Weight	0.70kg (1.52lb)
Dimensions	Ø129 x 110mm (Ø5.1" x 4.3")



*Design and specifications are subjects to change without notice.



INLGTO5IRWA

5.1MP Intelligent Lite ChromaView
IR Varifocal Turret Network Camera

Product Specifications



XLGJB03-H
Junction Box



XLGA01
Waterproof Joint



XLGJB07WM03-F
Wall Mount



XLGCM24
Ceiling Mount



XLGWM03-B
Wall Mount



XLGUP06
Pole Mount



XLGSE24
Pendant Mount



XLGSE24-A
Pendant Mount



VUSD256G
Micro SD Card

*Design and specifications are subjects to change without notice.

