

INSBO24IRCF

HD over Coax

2.4MP 1080P Bullet Camera with IR

- 2.4MP, 1/2.7" CMOS image sensor
- HD and SD dual-output
- Max. IR length 30m, Smart IR
- IP67, DC12V
- 120dB true WDR, 3DNR



Unify your Security Solution

The HD over Coax technology can support up to 4 signals transmitted over coaxial cable. With the dual-way data transmission the HD over Coax camera can interact with the STORM DVR by alarm triggers or control signals.

Long Distance Transmission

Long-distance and real-time transmission without any loss. It supports up to 800m for 1080P Full HD video via coaxial cable, and up to 300m via UTP cable.

Wide Dynamic Range

Embedded with industry leading wide dynamic range technology, vivid pictures are achieved even in the most intense contrast lighting conditions. True WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.



*Design and specifications are subjects to change without notice.



INSBO24IRCF

2.4MP 1080P Bullet Camera with IR

Product Specifications

Camera					
Image Sensor	1/2.7" 8 Megapixel progressive CMOS				
Effective Pixels	1928(H) x 1088(V)				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual 1/3 s-1/100,000 s				
Minimum Illumination	0.03 Lux / F2.0, 30IRE, 0 Lux IR on				
S/N Ratio	More than 65 dB				
IR Distance	Up to 30m (98feet)				
IR LEDs	18				
Camera Features					
Day/Night	Auto (ICR) / Manual				
Backlight Compensation	BLC / HLC / WDR (120dB)				
White Balance	Auto / Manual				
Gain Control	AGC				
Noise Reduction	2D / 3D				
Smart Illumination	Auto / Manual				
Lens					
Lens Type	Fixed Lens				
Mount Type	Board-in				
Focal Length	2.8mm				
Max. Aperture	F2.0				
Viewing Angle	H: 90°				
Pan/Tilt/Rotation	Pan: 0°-360°; Tilt: 0°-90°; D: 0°-360°				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8mm	40m (132ft)	16m (53ft)	8m (26ft)	4m (13ft)
Video					
Compression	H.265+; H.264+; MJPEG				
Resolution	1080P (1920x1080)				
Frame Rate	25/30fps at 1080P, 25/30/50/60fps at 720P				
Bit Rate	1-channel BNC HDCVI high definition video output & 1-channel BNC CVBS video output				
General					
Power Supply	12V DC ±25%; Less than 5W				
Working Environment	-30°C to +60°C (-22°F ~ +140°F) / Less than 90% RH				
Dimensions	164.7mm x 70mm x 71.6mm (6.48" x 2.76" x 2.82")				
Weight	0.97 lb (0.44 kg)				


*Design and specifications are subjects to change without notice.



INSBO24IRCF

2.4MP 1080P Bullet Camera with IR

Product Specifications



INSXBALUN
Balun



INSX134
Junction Box



INSX152
Pole Mount

Junction Mount	Pole Mount
INSX134	INSX134 + INSX152

*Design and specifications are subjects to change without notice.

