

# INSD04PTZ4X

## 4MP WDR 4x PTZ Network Camera

- 1/2.8" 4MP Progressive scan CMOS
- Powerful 4x optical zoom
- Supports triple-streams encoding
- WDR, Day/Night(ICR), Ultra DNR
- IP66, IK10
- Smart features such as face detection

### Unify your Security Solution

Its powerful optical zoom and its smooth control makes it an ideal choice to secure any areas.

### H.265 Decoding

STORM smart encoding technology can provide high-quality video with higher efficiency and can also reduce the cost of storage space and transmission adopting an advanced algorithm of auto stream control.

### Wide Dynamic Range

This camera offers vivid imaging in any scenario. Using industry-leading WDR technology, you'll be able to capture the subject in the most contrast lighting conditions.



\*Design and specifications are subjects to change without notice.



# INSD04PTZ4X

## 4MP WDR 4x PTZ Network Camera

## Product Specifications

Camera				
Image Sensor	1/3" 4 Megapixel CMOS			
Effective Pixels	2592(H) x 1520(V)			
RAM/ROM	256M/128M			
Scanning System	Progressive			
Electronic Shutter Speed	1/1s~1/30,000s			
Minimum Illumination	Color: 0.05Lux at F1.6; B/W: 0.005Lux at F1.6			
S/N Ratio	More than 50dB			
Camera Features				
Day/Night	Auto(ICR) / Color / B/W			
Backlight Compensation	BLC / HLC / WDR (120dB)			
White Balance	Auto / ATW / Indoor / Outdoor / Manual			
Gain Control	Auto/Manual			
Noise Reduction	Ultra DNR (2D/3D)			
Digital Zoom	16x			
Motion Detetion	Supported			
Region of Interest	Supported			
Privacy Masking	Up to 24 areas			
Lens				
Focal Length	2.7mm~11mm			
Max. Aperture	F1.6 - F2.8			
Viewing Angle	H: 112.5° ~ 30°			
Optical Zoom	4x			
Focus Control	Auto/Manual			
Pan/Tilt/Rotation	Pan: 0° ~ 355°; Tilt: 0° ~ 90°			
DORI	Detect	Observe	Recognize	Identify
Distance	180m(591ft)	72m(236ft)	36m(118ft)	18m(59ft)
Video				
Compression	H.265 / H.264 / MJPEG(Sub Stream)			
Resolution	4MP (2592×1520) / 3MP (2304×1296) / 1080P(1920×1080) 720P (1280×720) / D1 (704×576 / 704×480) / CIF (352×288/352×240)			
Frame Rate	Main stream: 4MP / 3MP / 1080P / 1.3MP / 720P (1 to 25/30fps)			
	Sub Stream: D1/CIF (1 to 25/30fps)			
	Third Stream: 720P / D1 / CIF (1 to 25/30fps)			
Bit Rate	448K ~ 8192Kbps			

\*Design and specifications are subjects to change without notice.



# INSD04PTZ4X

## 4MP WDR 4x PTZ Network Camera

## Product Specifications

PTZ	
Manual Control Speed	Pan: 0.1° ~100° /s; Tilt: 0.1° ~60° /s
Preset Speed	Pan: 100° /s; Tilt: 60° /s
Presets	300
PTZ Mode	8 Tours (up to 32 preset per tour)
Speed Setup	Human-oriented focal Length / speed adaptation
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/Tour if there is no command in the specified period
Intelligent Functions	
Smart Features	Tripwire, Intrusion, Abandoned/Missing, Face Detection
Event Trigger	Motion detection, Video tampering, Network disconnection, IP address conflict, Illegal access, Storage anomaly
Network	
Ethernet	RJ-45 (10XBase-T/100Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Compatibility	ONVIF Profile S&G, API
Video Management Software	STORM; STORM+; ARKIV
Storage	NAS; Local PC; Micro SD card up to 256GB
Maximum User Access	20 Users
Smart Phone	iOS, Android
General	
Power Supply	DC 12V/1.5A, PoE(802.3af)
Power Consumption	Less than 10W
Working Environment	-30°C to 60°C (-22°F ~ +140°F) / Less than 95% RH
Ingress Protection	IP66
Vandal Protection	IK10
Dimensions	Φ122 mm x 89 mm
Weight	1.46 lbs (0.66 kg)


\*Design and specifications are subjects to change without notice.



# INSD04PTZ4X

4MP WDR 4x PTZ Network Camera

## Product Specifications



**INSX200C**  
In-Ceiling Mount






**INSX137**  
Junction Box



**INSX203**  
Wall Mount



**INSX152**  
Pole Mount

Wall Mount	In-ceiling Mount
INSX203	INSX200C
	
Junction Box Mount	Pole Mount
INSX137	INSX152 + INSX203
	

\*Design and specifications are subjects to change without notice.

