

INSD08180IRF

4x2MP (8MP) H265 Network Multi-Lens IR Panoramic Dome W/IR W/SD Slot

- Four 1/2.8" 2 Megapixel progressive scan STARVIS™ CMOS
- Outputs max. 8MP (4096 × 1800) at 30 fps
- H.265+ & H.264+ flexible coding
- Built-in IR LED, max IR distance: 30 m
- Intelligent detection: Vehicle Analytics, Intrusion, tripwire
- Micro SD card up to 256 GB

Unify your Security Solution

Starlight Technology Improve your levels of security by using our Starlight technology. With its optical features, Starlight Technology will be able to balance all lighting throughout a scene. This will capture any colored details regardless of the lighting.

Smart H.265+ & H.264+

STORM smart encoding technology can provide high-quality video with higher efficiency and can also reduce the cost of storage space and transmission adopting an advanced algorithm of auto stream control.

On-board Analytics

This camera responds accurately to specific events in a given area. Our algorithm enables Tripwire violations, intrusion detection, abandoned/missing objects and much more. Facilitate your viewing experience using on the edge analytics – one product, multiple features.

LiteAI
Edge Analytics



*Design and specifications are subjects to change without notice.



INSD08180IRF

4x2MP (8MP) H265 Network Multi-Lens
IR Panoramic Dome W/IR W/SD Slot

Product Specifications

Camera				
Image Sensor	Four 1/2.8" 2Megapixel progressive CMOS			
Effective Pixels	4096 (H) × 1800 (V)			
RAM/ROM	2GB / 4GB			
Scanning System	Progressive			
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s			
Minimum Illumination	0.005 Lux at F1.6 (Color, 30IRE); 0.0005 Lux at F1.6 (B/W, 30IRE) 0 Lux (Illuminator on)			
S/N Ratio	More than 56 dB			
IR Distance	30 m (98.4 ft)			
IR LEDs	6			
Camera Features				
Day/Night	Auto(ICR) / Color / B/W			
Backlight Compensation	BLC / HLC / DWDR			
White Balance	Auto / Natural / street lamp / Outdoor / Manual / Regional Custom			
Gain Control	Auto / Manual			
Noise Reduction	3D DNR			
Smart Illumination	Supported			
Region of Interest	Yes (4 areas)			
Privacy Masking	4 areas			
Lens				
Lens Type	Fixed Lens			
Mount Type	M12			
Focal Length	2.8 mm			
Max. Aperture	F1.6			
Viewing Angle	Horizontal: 180.0° Vertical: 90.0°			
DORI Distance	Detect	Observe	Recognize	Identify
	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7m (25.3 ft)	3.9 m (12.8 ft)
Video				
Compression	H.265+, H.264+, H.265, H.264, MJPEG (only supported by the sub stream)			
Resolution	4096 × 1800; 3840 × 1680; 2880 × 1264; 1024 × 452; 1920 × 832; 1280 × 560			
Frame Rate	Main Stream: 4096 × 1800 (1–25/30 fps)			
	Sub stream: 1024 × 452 (1–25/30 fps)		Third stream: 1920 × 832 (1–25/30 fps)	
Bit Rate	H.264: 9 kbps–17664 kbps H.265: 9 kbps–17664 kbps			

*Design and specifications are subjects to change without notice.



INSD08180IRF

4x2MP (8MP) H265 Network Multi-Lens
IR Panoramic Dome W/IR W/SD Slot

Product Specifications

Lite AI	
Vehicle Analytics	Vehicle density; Parking space limit; Congestion alarm
People Counting	Crowd map; Global people counting; People counting in area
Smart Features	Intrusion, Tripwire
Audio	
Audio Compression	G.711A; G.711Mu; G.726; G.723
Audio I/O	1/1 RCA ports
Alarm	
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; scene changing; audio detection; intensity change; voltage detection; external alarm; safety exception; crowd distribution map; vehicle congestion; parking upper limit
Alarm I/O	2 channel in: 5mA 3V-5 VDC 2 channels out: 1,000mA 30 VDC/500mA 50 VDC
Network	
Network	RJ-45 (10/100/1000 Base-T)
SDK AND API	Yes
Cyber Security	Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade
Storage	NAS; SFTP; FTP; Micro SD Card up to 256 GB
Management Software	STORM, STORM+, ARKIV
Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP; Bonjour
Compatibility	ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec; P2P
Maximum User Access	20
General	
RS-485	1 (baud rate range: 1200 bps-115200 bps)
Power Supply	12V DC/24V AC/PoE(802.3at)
Power Consumption	Basic power consumption: 4.9W (12V DC); 6.4W(24V AC); 6.5W (PoE) Max. power consumption (ICR + IR LED): 12.5W (12V DC);14.3W(24V AC); 14.9W (PoE)
Working Environment	-40 °C to +60 °C (-40 °F to +140 °F); Less than 95% RH
Protection Grade	IP67; IK10
Dimensions	169.5 mm × Φ212 mm (6.7" × Φ8.3")
Weight	8 lbs (3.65 kg)


*Design and specifications are subjects to change without notice.



INSD08180IRF

4x2MP (8MP) H265 Network Multi-Lens
IR Panoramic Dome W/IR W/SD Slot

Product Specifications



INSX303
Wall Mount



INSX120
Junction Box



INSX111
Mount Adapter
(Included)



INSX150
Pole Mount



INSX140
Junction Box









INSX151
Corner Mount



INSX300
Ceiling Mount



INSXPARA
Parapet Mont

Ceiling Mount	Junction Mount
INSX111 + INSX300	INSX111 + INSX303 + INSX120
	
Power Box Mount	Pole Mount
INSX111 + INSX303 + INSX140	INSX111 + INSX303 + INSX150
	
Corner Mount	Parapet Mount
INSX111 + INSX303 + INSX151	INSX111 + INSXPARA
	



VUSD256G
Micro SD Card

*Design and specifications are subjects to change without notice.

