



LGNX16164KLN2T

16-Channel 4K NVR with 16-Port PoE, 2TB HDD



- 16-channel IP video input, up to 12 MP
- Video compression: H.265+/H.265/H.264+/H.264
- Incoming / outgoing bandwidth: 16 Mbps / 80 Mbps
- Simultaneous HDMI and VGA outputs
- 16 independent PoE network interfaces
- Camera-based intelligent functions (human/vehicle detection, perimeter protection, face recognition, etc.)

Dimensions



*Design and specifications are subject to change without notice - Version 2026-01-23

LGNX16164KLN2T - 16-Channel 4K NVR with 16-Port PoE, 2TB HDD

Video & Audio Input

IP Video Input

16-ch

Audio Input

1-ch, RCA

Video & Audio Output

HDMI

1-ch: 3840 × 2160 / 30 Hz, 1920 × 1080 / 60 Hz,
1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz

VGA

1-ch: 1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz,
1280 × 720 / 60 Hz

Audio Output

1-ch, RCA

Recording

Compression

H.265+/H.265/H.264+/H.264

Resolution

12MP / 8MP / 5MP / 4MP / 3MP / 1080P / 720P / D1 / CIF / QCIF

Bit Rate

64 Kbps to 10 Mbps

Playback & Backup

Playback Resolution

12MP / 8MP / 5MP / 4MP / 3MP / 1080P / 720P / D1 / CIF / QCIF

Decoding Capability

8-ch @ 1080P
3-ch @ 5MP
2-ch @ 8MP
1-ch @ 12MP

Synchronous Playback

8-ch

Playback Mode

Smart / Normal / Time Division / Label / Event / Picture / Log

Backup Mode

USB Device / Network

Advanced Features

Smart Detection

Area intrusion, line crossing, region entrance/region exiting, fast moving, object missing, unattended object, loitering detection, parking detection, face detection, people gathering detection, blurred detection, scene change detection, audio exception detection, human detection, vehicle detection, SMD, perimeter protection

Smart Playback

Face detection / Line crossing / Area intrusion / Motion / Human / Vehicle detection

Cloud Storage

Supported

Cloud Upgrade

Supported

Network

Incoming Bandwidth

160 Mbps

Outgoing Bandwidth

80 Mbps

Ethernet

1 × RJ-45 10 / 100 / 1000 Mbps self-adaptive

Network Compatibility

HTTPS, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF

Smart Phone

iOS (iPhone, iPad), Android (Phone, Pad)

Hard Disk

SATA

2 × SATA interfaces

Capacity

Up to 14 TB for each HDD

External Interface

PoE Interface

16 independent 10 / 100 Mbps PoE Ethernet interfaces

USB Interface

Front panel: 1 × USB 2.0
Rear panel: 1 × USB 2.0

Alarm Input / Output

4-ch / 1-ch

*Design and specifications are subject to change without notice - Version 2026-01-23

LGNX16164KLN2T - 16-Channel 4K NVR with 16-Port PoE, 2TB HDD

General

Power Supply
DC 54 V / 3.33 A

Power Consumption
≤ 15 W (without HDD and PoE)

Working Environment
-10 °C to +55 °C / 10 % to 90 % RH


Dimension (W × D × H)
326 × 243 × 52 mm

Weight
2.6 kg

Ordering Informations

- LGNX16164KLN2T - 2 To
- LGNX16164KLN4T - 4 To
- LGNX16164KLN6T - 6 To
- LGNX16164KLN8T- 8 To
- LGNX16164KLN10T - 10 To
- LGNX16164KLN12T - 12 To
- LGNX16164KLN16T - 16 To
- LGNX16164KLN20T - 20 To

Rear Panel



#	Item	#	Item
1	Power Switch	6	VGA Port
2	Power Input	7	Alarm Input
3	PoE Network Port	8	HDMI Port
4	USB Port	9	Audio Input/Output RCA
5	Network Port	10	Ground

*Design and specifications are subject to change without notice - Version 2026-01-23