


LGNX324KN

32-Channel 4K NVR



- **32-channel IP video input, up to 12 MP**
- **Video compression: H.265+/H.265/H.264+/H.264**
- **Incoming / outgoing bandwidth: 256 Mbps / 256 Mbps**
- **Dual asynchronous HDMI outputs (HDMI up to 4K) + simultaneous VGA output**
- **Up to 4 SATA interfaces (up to 18TB per HDD)**
- **Camera-based intelligent functions (human/vehicle detection, perimeter protection, face recognition, etc.)**

Dimensions



*Design and specifications are subject to change without notice - Version 2026-01-23

LGNX324KN - 32-Channel 4K NVR

Video & Audio Input

IP Video Input

32-ch

Audio Input

1-ch, RCA

Video & Audio Output

Video Output Mode

1 × VGA, 2 × HDMI

HDMI 1

Up to 3840 × 2160

HDMI 2

Up to 1920 × 1080

VGA

Up to 1920 × 1080

Audio Output

2-ch, RCA

Recording

Compression

H.265+/H.265/H.264+/H.264

Resolution

12MP / 8MP / 5MP / 4MP / 3MP / 1080P / 720P / D1 / CIF / QCIF

Playback & Backup

Playback Resolution

12MP / 8MP / 5MP / 4MP / 3MP / 1080P / 720P / D1 / CIF / QCIF

Decoding Capability

2-ch @ 12MP / 20 fps

4-ch @ 8MP / 30 fps

6-ch @ 5MP / 30 fps

8-ch @ 4MP / 30 fps

16-ch @ 1080P / 30 fps

Synchronous Playback

16-ch

Playback Mode

Smart Playback / Normal / Time Division / Label / Event / Picture

Backup Mode

USB / Network / eSATA

Advanced Features

Smart Detection

Area intrusion, line crossing, region entrance/region exiting, fast moving, object missing, unattended object, loitering detection, parking detection, face detection, people gathering detection, blurred detection, scene change detection, audio exception detection, human detection, vehicle detection, SMD, perimeter protection

Smart Playback

Face detection / Line crossing / Area intrusion / Motion / Human / Vehicle detection

Cloud Storage

Supported

Cloud Upgrade

Supported

Network

Incoming Bandwidth

256 Mbps

Outgoing Bandwidth

256 Mbps

Ethernet

2 × RJ-45 10 / 100 / 1000 Mbps self-adaptive

Network Compatibility

HTTPS, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF

Smart Phone

iOS (iPhone, iPad), Android (Phone, Pad)

Hard Disk

SATA

4 × SATA interfaces

Capacity

Up to 18 TB for each HDD

External Interface

USB Interface

Front panel: 2 × USB 2.0

Rear panel: 1 × USB 3.0

eSATA

1 × eSATA

RS-485

2

*Design and specifications are subject to change without notice - Version 2026-01-23

LGNX324KN - 32-Channel 4K NVR

Alarm Input / Output

16-ch / 4-ch

General

Power Supply

AC 100 ~ 240 V

Power Consumption

≤ 20 W (without HDD)

Working Environment

-10 °C TB +55 °C / 10 % TB 90 % RH

Dimension (W × D × H)

440 × 448 × 70 mm

Weight

6.1 kg

Ordering Informations

LGNX324KN4T - 4 TB

LGNX324KN8T- 8 TB

LGNX324KN10T - 10 TB

LGNX324KN12T - 12 TB

LGNX324KN16T - 16 TB

LGNX324KN20T - 20 TB

LGNX324KN24T - 24 TB


LGNX324KN28T - 28 TB

LGNX324KN32T - 32 TB

LGNX324KN36T - 36 TB

LGNX324KN40T - 40 TB

Rear Panel



Part	Name	Part	Name
1	Power Switch	6	eSATA Port
2	Power Input	7	VGA Port
3	Ground	8	Audio Input/Output RCA
4	Alarm Input	9	USB Port
5	HDMI Port	10	Network Port

*Design and specifications are subject to change without notice - Version 2026-01-23