


LGNXD06IRHEM

6.1 MP Fisheye Network Camera



- **High-definition imaging with a resolution of 6.1 MP**
- **Multiple dewarping mode**
- **Perimeter protection and people counting functions**
- **IR illumination up to 20 m**
- **IP67 water and dust protection**
- **Built-in microphone and speaker**

Dimensions



*Design and specifications are subject to change without notice - Version 2026-01-23

LGXDO6IRHEM - 6.1 MP Fisheye Network Camera

Camera

Image Sensor

1/2.5" Progressive Scan CMOS

Minimum Illumination

0.008 lux (Color); 0 lux (IR on)

Illumination Distance

IR: up to 20 m

Smart IR

Supported

Strobe Light

N/A

Lens

Focal Length

1.68 mm

Aperture

F2.0

Field of View

HORIZONTAL : 180°

VERTICAL : 180°

Mount

M12

DORI

Detection	Observation	Recognition	Identification
33 m	13 m	6.5 m	3.3 m

Compression

Video Compression

H.264 / H.264+ / H.265 / H.265+ / MJPEG

H.265 Codec Profile

Main

H.264 Codec Profile

Base / Main / High

Video Bit Rate

11 Kbps to 10 Mbps

Multiple Streams

N/A

Audio Compression

G.711A, G.711U

Audio Bit Rate

64 Kbps

Image

Maximum Resolution

2560 × 2560

Main Stream - Fisheye

50Hz: 25 fps (2560 × 2560, 1920 × 1920)

60Hz: 30 fps (2560 × 2560, 1920 × 1920)

Panoramic

50Hz: 15 fps (1920 × 1080, 1280 × 720)

60Hz: 15 fps (1920 × 1080, 1280 × 720)

4 PTZ

50Hz: 15 fps (1024 × 768)

60Hz: 15 fps (1024 × 768)

Fisheye + Panoramic + 3 PTZ

50Hz: 15 fps (1920 × 1920) + 15 fps (1920 × 1080) + 15 fps (1024 × 768) ×3

60Hz: 30 fps (1920 × 1920) + 15 fps (1920 × 1080) + 15 fps (1024 × 768) ×3

Fisheye + 4 PTZ

50Hz: 25 fps (1920 × 1920) + 15 fps (1024 × 768) ×4

60Hz: 30 fps (1920 × 1920) + 15 fps (1024 × 768) ×4

Fisheye + 4 PTZ

50Hz: 25 fps (1920 × 1920) + 15 fps (1024 × 768) ×4

60Hz: 30 fps (1920 × 1920) + 15 fps (1024 × 768) ×4

Panoramic + 4 PTZ

50Hz: 15 fps (1920 × 1080, 1280 × 720) + 15 fps (1024 × 768) ×4

60Hz: 15 fps (1920 × 1080, 1280 × 720) + 15 fps (1024 × 768) ×4

Sub Stream – Fisheye

50Hz: 25 fps (960 × 960, 480 × 480)

60Hz: 30 fps (960 × 960, 480 × 480)

Sub Stream – Panoramic

50Hz: 15 fps (704 × 576, 352 × 288)

60Hz: 15 fps (704 × 480, 352 × 240)

Sub Stream – 4 PTZ

15 fps (640 × 480)

*Design and specifications are subject to change without notice - Version 2026-01-23

LGNXDO6IRHEM - 6.1 MP Fisheye Network Camera

Image Settings

Parameters

Brightness / Contrast / Saturation / Hue / Sharpness

Shutter

Auto / Manual, 1/3 to 1/100000 s

Day / Night

IR Cut Filter

WDR

DWDR

Noise Reduction

3D DNR

Back Light Compensation (BLC)

Supported

High Light Compensation (HLC)

Supported

Region of Interest (ROI)

Supported

Smart Features

Basic Events

Motion detection, video tampering

Smart Events

Line crossing detection, area intrusion, region entrance, region exiting

Network

Storage

NAS (NFS, SMB/CIFS)

Protocols

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P

Compatibility

ONVIF (Profile S, G, T), CGI, SDK

Security

HTTPS encryption, IP address filtering, HTTP/HTTPS basic and digest authentication, TLS 1.1/1.2, WSSE

Users

40

Browsers

IE10, IE11; Chrome 57+; Firefox 52+

Mobile

iOS, Android

Active Deterrence

Red/Blue Light

N/A

Sound Warning

N/A

Interface

Network

1 × RJ45 10/100 Mbps

On-board Storage

Up to 256 GB

Microphone

Supported

Speaker

Supported

Audio Input / Output

1 / 1

Alarm Input / Output

1 / 1

Reset Button

Supported

General

Operating Conditions

-40 °C to 60 °C

Humidity

≤ 95% non-condensing

Power Supply

DC12V ± 25%

PoE

802.3at

Power Consumption

Maximum 9 W

Protection

IP67

Material

Metal

Dimensions


Ø152 × 53 mm

Weight

724 g

*Design and specifications are subject to change without notice - Version 2026-01-23

Accessoires



XLGNXJB18
Boîte de Jonction