

2MP IP Bullet Camera with IR

- 1/2.7" 2 Megapixel Progressive Scan CMOS
- H.265 & H.264 Dual-Stream Encoding
- Maximum 25/30FPS at 1080P (1920 × 1080)
- DWDR, Day/Night (ICR), AWB, AGC, BLC
- Multiple Network Monitoring: Web Viewer, STORM VMS
- 2.8mm Fixed Lens
- Maximum Length of IR LEDs: 30m
- IP67, PoE
- Outdoor / Indoor



Popular Mounting Solutions






Junction Box
INSX134





Corner Mount
INSX151



Pole Mount
INSX152

Corner Mount	Pole Mount
INSX134 + INSX151	INSX134 + INSX152
	
Junction Mount	
INSX134	
	

Dimensions (mm)



Technical Specifications

Camera					
Image Sensor		1/2.7" 2 Megapixel progressive CMOS			
Effective Pixels		1920 (H) x 1080 (V)			
RAM/ROM		256 MB / 32 MB			
Scanning System		Progressive			
Electronic Shutter Speed		Auto/Manual, 1/3~1/100000s			
Minimum Illumination		0.08Lux/F2.0 (Color, 1/3s, 30IRE), 0.3Lux/F2.0 (Color, 1/30s, 30IRE), 0Lux/F2.0 (IR on)			
S/N Ratio		More than 50dB			
IR Distance		Distance up to 30m (98ft)			
IR LEDs		18			
Camera Features					
Day/Night		Auto(ICR) / Color / B/W			
Backlight Compensation		BLC / HLC / DWDR			
White Balance		Auto / Natural / Street Lamp / Outdoor / Manual			
Gain Control		Auto / Manual			
Noise Reduction		3D DNR			
Digital Zoom		16x			
Privacy Masking		On/off (4 Areas, Rectangle)			
Lens					
Lens Type		Fixed			
Mount Type		Board-in			
Focal Length		2.8 mm			
Max. Aperture		F2.0			
Viewing Angle		H:104°, V:55°			
Optical Zoom		N/A			
Focus Control		Fixed			
Pan/Tilt/Rotation		Pan: 0°~360°; Tilt: 0°~90°; Rotation: 0°~360°			
DORI	Lens	Detect	Observe	Recognize	Identify
Distance	2.8mm	40m (131ft)	16m (52ft)	8m (26ft)	4m (13ft)
Video					
Compression		H.265 / H.264 / MJPEG (Sub Stream)			
Resolution		1080P (1920 × 1080) / 1.3MP (1280 × 960) / 720P (1280 × 720) D1 (704 × 576 / 704 × 480) / VGA (640 × 480) / CIF (352 × 288 / 352 × 240)			
Frame Rate		Main Stream: 1080P (1 ~ 25/30fps)			
		Sub Stream: D1 (1 ~ 25/30fps)			
		Third Stream: N/A			
Bit Rate		H.265: 12K ~ 6400Kbps; H.264: 32K ~ 10240Kbps			

* Design and specifications are subject to change without notice.

Technical Specifications

Audio	
Compression	N/A
Intelligent Functions	
IVS	Intrusion, Tripwire
Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal access, Storage anomaly
Network	
Ethernet	RJ-45 (10/100 Base-T)
Protocol	HTTP;HTTPS;TCP;ARP;RTSP;RTP;RTCP;UDP;SMTP; FTP;DHCP;DNS;DDNS;PP-PoE;IPv4/v6;QoS;UPnP; NTP;Bonjour;IEEE 802.1x;Multicast;ICMP;IGMP; TLS
Compatibility	API
Maximum User Access	10 Users / 20 Users
Smart Phone	IOS, Android
Interface	
Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A
General	
Power Supply	DC12V, PoE (802.3af)(Class 0)
Power Consumption	<5.5W
Working Environment	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Protection	N/A
Dimensions	Φ70mm × 64.7mm (2.76"x6.49")

* Design and specifications are subject to change without notice.