

16-Port PoE Switch with Gigabit Uplink



- Layer 2 management PoE switch
- PoE budget: 240W
- Support PoE, PoE+, Hi-PoE
- 250 meters long distance PoE transmission
- "Orange port" support Hi-PoE, can be used with the PoE extender
- PoE management, PoE Setting/Event Statistics/ Green PoE
- Search and upgrade via ConfigTool
- High lightning protection design
- Non-blocking video transmission

Technical Specifications

System	
Ethernet Port	2*10/100/1000 Base-T (Combo port); 2*1000 Base-X (Combo port); 16*10/100 Base-T (PoE power supply);
PoE Power consumption	Port1/2 support Hi-PoE (60W), PoE+, PoE Each power $\leq 30W$ Total $\leq 240W$
PoE Protocol	IEEE802.3af, IEEE802.3at, Hi-PoE
PoE Budget	240W
Switching Capacity	8.8G
Packet Forwarding Rate	5.36Mpps
Application Humidity	10%-90%
Power	AC 100~240V
Lightning Protection	Common Mode 4KV Differential Mode 2V
Working Temperature	-10°C~55°C
Weight	3.51kg
Dimension(WxDxH)	440mm x 300mm x 44mm

*Design and specifications are subject to change without notice.