

## IP Intercom Kit with Flush Mount



### Outdoor Station Features

- 1.3 Megapixels HD Camera
- Stainless Steel panel
- Night Vision
- Remote Intercom with the mobile application
- Surface mount and Flush mount
- IP54
- IK07

### Monitor Features

- 7" TFT Resistive touch screen
- IPC surveillance
- Alarm integration
- Embedded 4GB SD card
- Record & Snapshot

## Technical Specifications

### VUO2000A-C



System	
Main Processor	Embedded Micro Processor
Operating System	Embedded LINUX OS
Video	
Video Compression	H.264
Image Sensor	1/3" 1.3 Megapixel CMOS scan
Lens	2.8mm
Angle of View	D: 120° / H: 90°
Day/Night	Color Image
Audio	
Audio Compression	G.711
Audio Input	Omnidirectional Microphone
Audio Output	Built-in Speaker
Bidirectional Talk	Supported
Operation Mode	
Keypad	Single Mechanical Button
Network	
Ethernet	10/100 Mbps Self-adaptive
Network Protocol	TCP/IP
Interface	
Door Control	2 Channels
Alarm In	2 Channels
RS485	1
General	
Ingress Protection	IP54, IK07
Tamper Switch	1
Installation	Surface & Flush
Material	Stainless Steel
Power Consumption	DC 12V; Standby ≤1W, Working ≤10W
Working Environment	-40°C - +60°C
Dimensions	130mm x 32.2mm x 140mm
Weight	0.8Kg

\* Design and specifications are subject to change without notice.

## Technical Specifications

### VUH1560B



System	
Main Processor	Embedded Micro Processor
Operating System	Embedded LINUX OS
Video	
Video Compression	H.264
Screen	7" 800x480, Capacitive
Audio	
Audio Compression	G.711
Audio Input	Omnidirectional Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Supported
Operation Mode	
Keypad	Touch Buttons
Network	
Ethernet	10/100 Mbps Self-adaptive
Network Protocol	TCP/IP
Interface	
Alarm In	8 Channels
Alarm Out	N/A
RS485	N/A
General	
Memory Slot	Embedded 4GB
Installation	Flush
Power Consumption	DC 12V, Standby $\leq 1.5W$ , Work $\leq 7W$ ; Supply Directly by VUNS1060A
Working Environment	-10°C - +55°C
Dimensions	221.2mm×154.3mm×24.2mm
Weight	0.8Kg

\* Design and specifications are subject to change without notice.